



Fount Solution H-UV/H-UV L (LED)

K-Supply

K-Supply Fount Solution H-UV/H-UV L (LED) is an additive for H-UV and H-UV L (LED) offset printing presses. This product, tried and tested at the Komori Graphic Center-Europe, is highly effective.

Benefits


- Suitable for I.P.A.-free printing.
- Very clean circulating water.
- Protects against bacterial contamination.
- Aids the fast drying of H-UV L (LED) inks.

Directions

Use plastic pumps only.

Specifications

Product name	K-Supply Fount Solution H-UV/H-UV L (LED)
Application	Sheetfed offset, water with Hydrogenkarbonat < 200mg/l
Additional dosage	3 - 4 %, 0 - 5 % with Isopropylalkohol
Conductivity	6,5mS in the concentrate, circa 210µS / (1 % addition) into the solution.
Colour	Blue
Density	1,03 g/cm ³
Flashpoint	> 63 °C
pH-value	4,8 - 4,9 in the concentrate. 4,7 - 5,5 depending on water quality and additional dosage in the dilution of the used fount solution.
Storage conditions	0 - 35 °C, do not expose to direct sunlight.
Packaging	20 Kg Can

 **Directions for Use:**
For details, please refer to the safety data sheet.

KOMORI INTERNATIONAL (EUROPE) B.V.

Reactorweg 151, 3542 AD Utrecht, The Netherlands, Tel: +31 (0)88 177 07 07

www.komori.eu

C/FSH | EN | 1P | NL | 3 | 2020.11 | 500 | KIE