

Multi Fount Solution



K-Supply Multi Fount Solution is an additive for offset printing presses, especially suitable for H-UV/H-UV L (LED) printing presses. This product, tested at the Komori Graphic Center-Europe, is highly effective.

Benefits

- Suitable for I.P.A.-free printing.
- Low foam.
- Very clean circulating water.
- Protects against bacterial contamination.
- Good compatibility with sensitive printing plates.

Directions

Use plastic pumps only when decanting K-Supply Multi Fount Solution.

Specifications

Product name	K-Supply Multi Fount Solution
Application	For sheetfed offset, all water qualities.
Additional dosage	3 %, with 0 - 5 % Isopropylalkohol, maximum of 5 % recommended 4 % without Isopropylalcoho.
Conductivity	5,5mS - 6,5mS in the concentrate, circa 465µS / 1 % addition into the solution.
Colour	Yellow
Density	1,11 kg/l
Flashpoint	>63 °C
pH-value	4,70 - 4.85 in the concentrate. 4,80 - 5,20 depending on water quality and additional dosage in the dilution of the used fount solution.
Storage conditions	0 - 35 °C, do not expose to direct sunlight.
Packaging	20 Kg Can

Directions for Use: For details, please refer to the safety data sheet.

Reactorweg 151, 3542 AD Utrecht, The Netherlands, Tel: +31 (0)88 177 07 07